



- PowerCart Component (~575-675 pcs/week)
- PowerCart: 25 with 3'Wx8'L table top
 - Track: ~350ft
 - Charge Rail: 5 units (15 minutes)
 - Cart on Demand: 3 units
 - Display Monitor: 1 unit
 - Mini Laptop: 1 unit
 - Tunnel/PowerCart Communication: 5 cells
 - Loading Station: 1 unit

Stain Tunnel: 3 minute cure

System uses 24 Halogen elements controlled by a touch screen control panel with two heat zones. A timed motion sensor activates the system when carts enter. Side heat zone uses 8:1 IR sensor to monitor and control part temperatures. Air temperature is controlled by a Thermocouple. A 10" exhaust blower removes fumes.

POWER: 44kW @480V 3ph ~64Amps

Sealer and TopCoat Tunnels: 6 minute cure

System uses 48 Halogen elements controlled by a touch screen control panel with three heat zones (2 side heat zones and one convection zone). A timed motion sensor activates the system when carts enter. All side heat zones uses 8:1 IR sensors to monitor and control part temperatures. Air temperature is controlled by a Thermocouple. A 10" exhaust blower removes fumes.

POWER: 88kW @480V 3ph ~128Amps

- Cart Programmer**
has 9 program buttons to load system program operation into each cart.
- System Monitor**
shows all cart battery levels and has a system On/Off switch
- Diagnostic Laptop**
- Cart on Demand**
- In-line Charge Rail**

<p>THIS DRAWING IS THE PROPERTY OF PRIME HEAT AND SHALL NOT BE COPIED OR REPRODUCED IN TOTAL OR IN PART WITHOUT THE EXPRESSED PERMISSION OF PRIME HEAT.</p> <p>THIS DRAWING WAS PREPARED WITH THE SOLE INTENT AS A GUIDE FOR THE PURPOSE OF THE INHOUSE MANUFACTURE OF A PRODUCT AND THE MAINTENANCE THEREOF.</p> <p>IT IS THE RESPONSIBILITY OF THE CONSUMER TO INSURE THAT ONLY QUALIFIED ELECTRICAL PERSONNEL UTILIZE THIS DOCUMENT.</p>	JOB NUMBER T. Lin 8/20/2012	1844 Friendship Drive El Cajon, CA 92020 (619) 449-6623 www.primeheat.biz	TITLE PowerCart System	REV 1	
	CHECKED SCALE NONE				
	SHEET 1 OF 1	DWG No. Conceptual Drawing			